AD Force M775 (AD-38x)

Overview

Frequency Band UHF 860 - 960 MHz

Chip Impinj M775

IC Attachment Technology Strap Attach

Antenna Dimensions 50 x 30 mm / 1.969 x 1.181 in

International Standard ISO 18000-63 TYPE C

Industry Segments Apparel Logistics

Applications
Brand Protection
Home Essentials
Supply Chain Management

RoHS EU Directive 2011/65/EU and Directive (EU) 2015/863 Compliant

REACH Regulation (EC) No. 1907/2006



Next-gen apparel tag with high read sensitivity and crypto capabilities for ultimate brand protection

AD Force M775 is the next generation of Avery Dennison's popular 50×30 mm apparel tag, featuring the Impinj M775 crypto chip.

Impinj M775 tag chip is a high-performance RAIN RFID tag chip with an ISO/IEC 29167-11 based cryptographic engine and a unique Impinj programmed cryptographic key. Together with the **Impinj Authentication Service** it enables cryptographic authentication of tagged items. This valuable feature helps to reduce the spread of counterfeit goods in the global market by authenticating each RFID tagged item automatically in real time as it travels through the supply chain.

The M775 IC memory configuration includes 128 bits of EPC memory and 32 bits of user memory. The chip is also equipped with a 96 bit TID with a 48-bit serial number.

The chip offers increased sensitivity and improved readability over previous generation Impinj ICs, such as Monza R6.

The product is currently offered in dry and wet formats with a 40# paper antenna carrier, as well as a thermal transfer printable paper label.


The inlay is compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, especially in the retail environment. It is manufactured according to the industry's highest quality standards, as confirmed by the RFID Lab at Auburn University, which awarded Avery Dennison its first ever ARC accreditation for overall quality.




Technical features

| Chip | Impinj M775 | Impinj M775 | | |
|-----------------------|---|---|---|--|
| EPC and User Memory | 128-bit EPC, 32-bit User Memory | | | |
| TID Memory | 96-bit / 48-bit unique seri | 96-bit / 48-bit unique serial number | | |
| Product Code | RF602646NPD | RF602647NPD | RF101234NPD | |
| Delivery Format | Dry inlay + | Wet inlay | Label | |
| Die-Cut Dimension | - | 53 x 33 mm / 2.087 x 1.299 in | 53 x 33 mm / 2.087 x 1.299 in | |
| Inlay Substrate | 40# Paper | 40# Paper | 40# Paper | |
| Face Sheet | _ | - | TT2C (FASSON®) Bright White | |
| Total Thickness | 11.5 - 13.5 mils / 292 - 342 microns | 12.7 - 14.7 mils / 322.58 - 373.38 microns | 16.2 - 18.2 mils / 411.48 - 462.28 microns | |
| Standard Pitch | 40.64 mm / 1.6 in | 40.64 mm / 1.6 in | 40.64 mm / 1.6 in | |
| Web Width | 58.0 mm / 2.283 in | 58.0 mm / 2.284 in | 58.0 mm / 2.284 in | |
| Core Size | 76 mm / 3 in | 76 mm / 3 in | 76 mm / 3 in | |
| Quantity / Reel | TBD pcs/reel | TBD pcs/reel | TBD pcs/reel | |
| Size of Roll | 15.5" MAX OD | 13" MAX OD | 8" MAX OD | |
| Operating Temperature | -40 °C to 85 °C / -40 °F to | -40 °C to 85 °C / -40 °F to 185 °F | | |

Orientation sensitivity




Read range



All graphs are indicative: performance in real life applications may vary.

Contact information

rfid.averydennison.com/contact +1-678-617-2359













© 2022 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only

Warranty: Please refer to Avery Dennison standard terms and conditions: rfid.averydennison.com/termsandconditions

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.



Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.