

GVision LCD Monitor L7VH-TS Vista Clear Series

- Product Specification -

Configuration	L7VH-TS	
LCD Display	17.0" TFT active matrix panel	
Display Size	337.9(H)x270.3(V) mm	
Pixel Pitch	0.264(H)x0.264(V) mm	
Max. Resolution	SXGA 1280x1024	
Contrast Ratio	350:1 (typical)	
Brightness	250 cd/m ² (typical)	
Response Time	20 ms	
Display Color	16M	
Viewing Angle	L/R	+80°~-80° = 160 total range
	U/D	+80°~-80° = 160 total range
PC Interface	Video	RGB analog 0.7V peak to peak
	Sync.	TTL positive or negative
	Display Mode	VGA 720x400 (70 Hz)
		VGA 640x480 (60/70/72/75 Hz)
		SVGA 800x600 (56/60/72/75 Hz)
	XGA 1024x768 (60/70/75 Hz)	
	SXGA 1280x1024 (60/75 Hz)	
	Input Connector	D-sub 15 pin
Video Interface Optional Module	Video Input	Composite (CVBS) Video; Y/C Separated
	Input Connector	RCA for CVBS
		4-Pins S Terminal for Y/C
TV Tuner Optional Module	Receiving Channel	181 MTS CH (113 CATV)
	Input Connector	F type Jack
	Audio Output	3.5 mm Mini Stereo Connector
Audio Interface	Amplify	Building Internal Audio Amplify
	Input Connector	3.5 mm Mini Stereo Connector
	Speaker	2W / per channel driver
Front Control	Power on/off with LED, Menu, Select, Adjustment (+,-)	
Remote Control	32 Keys Full Function Remote Control	
PIP (Picture in Picture)	Video on PC mode .or. TV on PC mode	
Plug & Play	DDC1/2B compatible	
Power Adapter	Input AC 90~264V, 50~60Hz; Output DC 12V / 3.5A	
Operating Conditions	Temperature	5°C-35°C (41°F-95°F)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C-60°C (-4°F-140°F)
	Humidity	10%-90% (no condensation)
Optional Module	Adjustable Arm	
Certification	C-UL, FCC, CE, TUV/GS, BSMI, EPA, NUTEK, TCO	

* Specifications are subject to change without notice.

Rev. 0.0



Catch the wave of the future - Now!

GVision Incorporated
 20532 Crescent Bay Drive, Suite 104
 Lake Forest, CA 92630
 Tel: 949.586.3338
 Fax: 949.586.3398

