

# POS X

POINT OF SALE  
SIMPLIFIED

# EVO HiSpeed

## Thermal Receipt Printer

The EVO HiSpeed Thermal Receipt Printer sets the bar in both speed and reliability. Engineered to operate day-in and day-out in the harshest of environments, the EVO HiSpeed provides the steadfast performance you need. Perfect for high-volume retail and hospitality operations, the EVO HiSpeed features lightning quick receipt printing, JamFree Autocutter Technology, and is backed by the best warranty in the industry.




### Key Features

- Extreme performance 300 mm/sec print speed
- Power supply and interface cable(s) included
- Drop-in easy thermal paper loading
- JamFree AutoCutter technology
- ESC/POS and OPOS compatible
- Wall-mountable
- 5-Year Warranty includes 2-Day Advance Exchange service

receipt printer

# EVO HiSpeed Thermal Receipt Printer Specifications

PART NUMBER	EVO-PT3-1HU	EVO-PT3-1HUP	EVO-PT3-1HUS	EVO-PT3-1HUE
<b>SPECIFICATIONS</b>				
Interfaces	USB	USB/Parallel	USB/Serial	USB/Ethernet
Interface Details	USB 2.0	USB 2.0/IEEE-1.284	USB 2.0/RS-232C	USB 2.0/(10/100)
Emulation	ESC/POS Command Compatible			
Print Method	Direct Thermal			
Printing Speed	11.81"/sec (300mm/sec)			
Dot Density	180 DPI x 180 DPI			
Printing Direction	Unidirectional with Friction Feed			
Sensors	Cover Open, Paper Low, Paper End			
<b>CASH DRAWER PORTS</b>	2 Circuits (24 V, 1 A max)			
<b>RELIABILITY</b>	TPH Life 99.42 miles MCBF 60,000,000 Lines			
<b>PAPER</b>				
Type	Thermal Paper			
Width	1.9" (50 mm) - 3.15" (80 mm)			
Thickness	0.002" (0.06 mm) - 0.0035" (0.09 mm)			
Roll Diameter	Max 3.27" (83 mm)			
Roll Core Inner Diameter	0.492" (12.5 mm) ± 0.019" (0.5 mm)			
<b>CHARACTER SET</b>	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page) International Characters 14			
<b>CHARACTER/LINE</b>	Font A (12 x24) 42 columns		Font B (9 x17) 56 columns	
<b>BARCODES SUPPORTED</b>	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, PDF 417(2D)			
<b>AUTO CUTTER</b>				
Type	JamFree auto-retracting guillotine			
Life	1,500,000 Cuts			
Cutting Method	Full/Partial Cut			
<b>PHYSICAL</b>				
Dimension	6.1"(w) x 8"(d) x 6.1"(H)			
Weight	3.7 lbs			
Color	Black			
<b>ELECTRICAL</b>	100-240 VAC 50/60 Hz (input)		24 VDC/1.5 A (output)	
<b>ENVIROMENTAL</b>				
Temperature	41°F to 104°F operating -4°F to 140°F storage			
Humidity	35%-80% non condensing (operation)		10%-90% non condensing (storage)	
<b>WARRANTY</b>	5-Year includes 2-Day Advance Exchange Warranty Service, 2-Year on Autocutter and Print Head			
<b>CERTIFICATIONS</b>	FCC, MIC, UL, CE, CCC, RoHs			
<b>OPERATING SYSTEM</b>	WIN 95/WIN 98/WIN 2000/WIN XP/VISTA/Win 7/Win 8/OPOS drivers available			



<b>ACCESSORIES</b>	
1CARDP	Parallel Interface Card for EVO HiSpeed
1CARDS	Serial Interface Card for EVO HiSpeed
1CARDE	Ethernet Interface Card for EVO HiSpeed
ZWE-CRW	2-Year Warranty Extension
ZOE-CRW3	3-Year Overnight Exchange
ZOE-CRW5	5-Year Overnight Exchange