



The EVO TM4 Touch Screen Monitor features features state-of-the-art Tru-Flat Resistive Technology. The zero bezel design eliminates the frame found on traditional monitors, creating a seamless, smooth surface. The screen is easy to clean and is resistant to water, dust, grease, and food build-up, thus making it the ideal choice for retail or restaurant settings. The TM4's aluminum alloy frame and stand can withstand the harshest of environments.




• IP54 Rating - Resistant to dust buildup and splashing water

• 3 Year Advanced Replacement Protection comes standard

• Sturdy die-cut aluminum alloy frame provides bump-free operation

EVO Touch Monitor Specifications

PART NUMBER	EVO-TM4A	EVO-TM4C
PANEL SIZE	15" TFT Active Matrix Display	
Bezel Type	Standard	Tru-Flat
Touch Screen	5-Wire Resistive, 50 millions taps per location	
Max Resolution	1024 X 768	
DISPLAY		
PC Video Interface	Analog RGB (VGA)	
Brightness	250 nits	
Colors	16.7 million colors	
Controls	Power on/off , auto adjustment(+/-)	
Viewing Angle	160°	
Housing	Die Cut Aluminum	
PHYSICAL		
Dimensions	14.21"(W) x 9.79"(H) x 13.27"(D)	
Weight	14.33 lbs	
USB	1x USB 2.0 (TypeA), 1x USB 2.0 (Type B to PC)	
Serial/COM	2 x COM 1 xDB-9/F (to PC), 1 x RJ-45 (to VFD)	
Tilt Angle	0° to 90°	
Housing Color	Black	
Stand Style	Cable Management Base	
Mounting Options	Desktop Placement, VESA 100mm x 100mm	
ELECTRICAL		
Adapter Output	36W 12 V, 3A	
ENVIROMENTAL		
Ingress Protection Rating	IP54 - Resistant to dust buildup and splashing water	
Temperature Operating	32°F to 104°F	
Humidity	5% - 95% non-condensing	
WARRANTY	3 Year Limited	
CERTIFICATIONS	FCC Class A, CE, LVD, RoHs	
OPERATING SYSTEM	DOS/WIN NT 4/WIN 9X/WIN ME/WIN 2000/WIN CE/XP/VISTA/WIN 7/Linux	



ACCESSORIES		
EVO-MR4-U	3 Track MSR with USB interface	
EVO-BR4	Inegrated Bio Reader	
EVO-RD4-LCD8	Integrated Rear Display, 8.4" LCD, VGA	
EVO-RD4-VFD	Integrated Rear Display, VFD	
EVO-XZ4-M100	XZ4-M100 Universal VESA Mount for All TouchPC & Touch Monitors	