

# POSX

POINT OF SALE  
PERFECTED

## Xp8200

### CUSTOMER POLE DISPLAY

The Xp8200 Pole Display was designed to blend in beautifully with your POS Station. Beyond its great looks, the lack of dip switches make configuration through the provided software a breeze. Featuring OPOS support and several popular emulations, including Epson, CD-5220, and UTC, the Xp8200 makes a great addition to any POS station. Larger than industry average characters and adjustable height stand round out the Xp8200's features.



### KEY FEATURES

- Ideal vertical display for smaller counter spaces
- 10 Standard display emulations and OPOS
- 2-line, 20-character per line display
- Adjustable height and pitch angles
- USB and RS232 Interfaces
- 1 year warranty

CUSTOMER DISPLAY

# Xp8200 Series Specifications

|                        |  |
|------------------------|--|
| <b>PART NUMBER</b>     | XP8200B  |
| <b>INTERFACE</b>       | USB, RS-232 db9 female   |
| <b>DISPLAY</b>         |  |
| Type                   | Vacuum Fluorecent Display  |
| Display Pattern        | 5 x 7 dot matrix   |
| Brightness             | 300-700 cd/m <sup>2</sup>  |
| Character Type         | 95 Alphanumeric and 32 International   |
| Character Size         | 0.207" (w) x 0.366" (H)  |
| Character Number       | 20 per row x 2 Rows  |
| Emulations             | EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL, LD-220 |
| <b>PHYSICAL</b>        |  |
| Weight                 | 2.3 lbs  |
| Dimensions Panel       | 8.7" (w) x 1.97" (D) x 3.38" (H)   |
| Dimensions Base        | 8.5" (w) x 4.17" (D) x 1.38" (H)   |
| Extensions             | 2 x 5.127"   |
| Viewing Angle          | Maximum 90°  |
| Pitch Angle            | Maximum 30°  |
| Horizontal Rotation    | Maximum 360°   |
| Interface Cable Length | 5'   |
| Color                  | Black  |
| <b>ELECTRICAL</b>      |  |
| Power                  | 5V, 1A   |
| <b>ENVIORNMENTAL</b>   |  |
| Temperature            | 32° F to 114° F operating  |
| Humidity               | 10% - 95% non-condensing   |
| Drop Resistance        | Multiple drops from 3.3' onto a concrete surface   |
| <b>WARRANTY</b>        | 1 Year Limited   |

