



CARE . TRUST . RESPONSIBILITY

POS TERMINAL SP-2600 SERIES

THE TRANSFORMER WITH 999+ CONFIGURATION



Tier 1 and Tier 2 retail and chain stores need to leverage outstanding experiences at every touchpoint to win customer loyalty. Take advantage of the opportunity to wow customers at the point of sale (POS) with the Partner Tech SP-2600. We've nicknamed it the "Transformer" for its superior configurability, scalability, and power.

The SP-2600 allows you to choose from three sizes for dual widescreens (11.6", 15.6" and 18.5") to optimally display your POS system interface as well as messaging on the customer-facing side for barrier-free communication. The displays are controlled independently, so you can show the same screen or different screens at the checkout. The i5/i7 model supports up to three independent displays, with the option to support digital signage.

Both the front-facing and customer-facing display have integrated MSR and 2D barcode readers. This feature allows customers to swipe loyalty or payment cards and scan barcode or QR codes on coupons and offers sent to their smartphones without assistance from a sales associate.

As consumers become more accustomed to technology in their daily lives, the POS is evolving into a multimedia center. The modularized SP-2600 "Transformer" gives you options to optimize the checkout and payment transaction experience to reflect your tech-savvy, forward thinking brand.

SPECIAL FEATURES

Powerful Intel® 6th generation Skylake platform (Celeron/i3/i5/i7)

Highly customizable for maximum versatility: available in single and double-screen configurations. Ideal for high-customer interaction and kiosk applications.

Transformable terminal available in 3 screen sizes (18.5"/15.6"/11.6")

Bezel-free screen with projected capacitive touch (multi-touch)

Supports rich I/O

OPTIONAL

Optional powered USB (3x12v, 1x24v)
Expansion options: 1 Mini PCIe & WLAN Module

Optional integrated peripherals: MSR, NFC, 2D scanner, Bio reader, smart card reader, camera

SP-2600 SERIES

Item	SP-2600 IoT Ready	SP-2600 IoT Advanced
CPU	6th Generation Sky Lake - H110 Chipset Celeron G3900 (2.8GHz, Dual Core, 2M Cache) i3-6100 (3.7GHz, Dual Core, 3M Cache)	6th Generation Sky Lake - Q170 Chipset i5-6500TE (up to 3.3GHz, Quad Core, 4M Cache) i7-6700TE (up to 3.4GHz, Quad Core, 8M Cache)
Memory	DDR4 SODIMM (2133 MHz), 2x Memory Standard Spec: 4GB, 8GB	
Storage	Internal 2.5" SATA BAY x 2 HDD Standard: 500 GB x 1 (Default) SSD Selection Standard: 32 GB / 64 GB / 128 GB	
External I/O Interface	2 * Serial ports, RS232 (DB9), RI/5V/12V selection by BIOS (COM1, COM2) 2 * Serial ports, RS232 (RJ45), RI/5V/12V selection by JP (COM3, COM4) 1 * RJ11 port supports 2 cash drawer with 24V 1 * DC+12V out 4 * USB 3.0 1 * DC +12V input power-jack 1 * Audio (1 * Line-out 1) 1 * HDMI port 1 * VGA 2 x RJ45 LAN (IEEE 802.3 10/100/1000 Mbps Ethernet)	
External I/O Options	2nd VGA x 1 Powered USB 12V x 3 & 24V x 1 Parallel Port	
Expansion Slot	1 * Mini-PCIe slot	
RAID Function	N/A	On-Board
Display Support	Dual Independent Displays	Triple Independent Displays
Intel AMT	N/A	YES
OS	Window 7, POS Ready7, Window 8.1, Windows 8.1 Industry Pro Retail , Windows 10, Linux (Ubuntu)	

Item	SP-2611	SP-2615	SP-2618
Display	11.6"1366x768	15.6"1366x768	18.5"1366x768
Touch	Projected capacitive touch (Multi Touch)		
Speaker	1*3W		
Optional Peripherals	Dual Display 11.6", 15.6", 18.5" 3 tracks magnetic reader(USB interface) 2D Barcode Scanner ** Support 3 out of 4 Peripherals coexist as below: Biometric Reader or I-Button, RFID reader (NFC) (Factory Option) Smart Card Reader Camera 2.0M (Factory Option) - Either for Front or 2nd Screen only		

*Specification is subject to change without prior notice



PARTNER TECH USA INC.
15320 Barranca Parkway Suite 150.
Irvine, CA 92618
TEL: +1-949-598-1888
sales@partnertechcorp.com

