

sewoo

Advanced Desktop Label Printer

LK-B301IE



- Excellent Compatibility with industry standards
- Ultra Compact and Durable
- Easy to use and maintain
- Optional Auto cutter, Peeler, Wireless Interface (Wi-Fi, Bluetooth)
- Supports label design software "Label Cooker"
- Versatile Font Types & Barcodes Printing Supported



WiFi



Bluetooth



Barcode




Durable



Easy Loading



Fast Speed



Compact Design



Easy Replacement



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
152mm/sec

Print Width
108mm (4.25")

Resolution
203 DPI (8 dots/mm)

Memory
Main Flash 1MB
SDRAM 16MB
FONT Flash 8MB

Sensor
Gap, Black mark, Cover open

Power
Type : External SMPS
AC : 100~240Vac, 2.0A, 50~60Hz
DC : 24Vdc 2.5A



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
7.48" x 10.31" x 6.61"
(190 x 262 x 168 mm)

Weight (Kg)
1.52kg



MEDIA CHARACTERISTICS

Media Type
Roll, Fanfold, Blackmark,
Continuous, Gap, Punched hole,
Notch Sensor

Media Width
25.4~115mm

Media Roll Diameter
Up to 127mm (5")

Media Core Diameter
25.4mm (1")

Thickness
0.060~0.20mm



OPERATING CHARACTERISTICS

Operating Temperatures
5 ~ 40°C

Operating Humidity
25 ~ 85%

Storage Temperature
-20 ~ 60°C

Storage Humidity
10 ~ 90%



BARCODES

1D
Code39, Code128 with subsets
A/B/C/Auto, UCC/EAN-128, Code93,
Codabar, Interleaved 2 of 5, UPC-A,
UPC-E, UPC-A and E with 2 or 5 digit
extension, EAN-8, EAN-13, EAN-8 and
13 with 2 or 5 digit extensions,
Postnet, Plessey, MSI-3, German Post
CodeLogmars, Code11,
UPC_Interleaved 2 of 5, Industrial
2 of 5, Standard 2 of 5, Planet, ANSI,
Logmars

2D
MaxiCode, PDF 417, Data Matrix,
QR Code, MicroPDF417, AZTEC,
Code 49, CODABLOCK, RSS



SOFTWARE

Emulations
EPL II, ZPL II Command compatible

Drivers
Windows Driver
Linux Driver

Mac Driver

SDKs
Windows SDK
Android SDK
iOS SDK



INTERFACES

Standard
USB, Serial(RS-232C), Ethernet

Optional
Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready (Bluetooth4.2+BLE)



CERTIFICATIONS

CE, FCC, KC, UL, CB



FONTS / GRAPHICS

EPL II
6 bitmapped
8x12, 10x16, 12x20, 14x24, 32x48,
24x24(KSC5601)

ZPL II
9 bitmapped
5×9, 7×11, 10×18, 10x18, 15×28,
13×26, 40×60, 13x21, 24x24
2 smooth scalable(English, Korean)



ACCESSORIES

Standard
Power Cord, Power Supply,
Interface Cable(USB, Serial)

Optional
Auto cutter, Peeler

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprinter.com

