

sewoo

Desktop Label Printer

LK-B425



- Fast Print Speed : 6 ips
- Excellent Compatibility
- Easy to use and maintenance
- Ultra Compact design for various KIOSK
- Support label design software "Label Cooker"
- Option : Auto-cutter, External paper supply



WiFi



Bluetooth



Barcode



Durable



Easy
Loading



Fast
Speed



Compact
Design



Easy
Replacement



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 2.3ips(152mm/sec)

Print Width

Up to 4.1”(104mm)

Resolution

203 dpi (8dots/mm)

Memory

1MB Main Flash, 16 SDRAM,
8MB Font flash

Sensor

Gap, Black mark, Cover open

Power

Type : External SMPS

AC : 100~240Vac, 1.5A, 50/60Hz

DC : 24Vdc/1.75A

Auto-cutter(Optional)

Type : Guillotine

Life : 200,000 Cuts, Max 20 cycle/1 min



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

7.16” x 4.72” x 4.48”

(182 x 120 x 123 mm)

Weight (Kg)

3.3lb(1.5kg)



MEDIA CHARACTERISTICS

Media Type

Roll, Fanfold, Blackmark,
Continuous, Gap, Notch Sensor

Media Width

0.9”~4.4”(25 ~ 114mm)

Media Core Diameter

Ø 1”(25.4mm)

Ø 1.5”(38.1mm)

Media Roll Diameter

Internal : Ø 25.4(1”) or

Ø 38.1mm(1.5”)

External : Ø 127mm(5”)

Thickness

0.065~0.20mm



OPERATING CHARACTERISTICS

Operating Temperature

32 ~ 104°F(0 ~ 40°C)

Operating Humidity

10 ~ 90%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%



BARCODES

1D

Code39, Code128 with subsets
A/B/C/Auto, UCC/EAN-128,
Code93, Codabar, Interleaved 2
of 5, UPC-A, UPC-E, UPC-A and E
with 2 or 5 digit extension, EAN-8,
EAN-13, EAN-8 and 13 with 2 or 5
digit extensions, Postnet, Plessey,
MSI-3, German Post CodeLogmars,
Code11, UPC_Interleaved 2 of 5,
Industrial 2 of 5, Standard 2 of 5,
Planet, ANSI, Logmars

2D

MaxiCode, PDF 417, Data Matrix,
QR Code, MicroPDF417, AZTEC,
Code 49, CODABLOCK, RSS



SOFTWARE

Emulations

EPL II, ZPL II Command compatible

Drivers

Windows Driver

Linux Driver

Mac Driver

SDKs

Windows SDK

Android SDK

iOS SDK



INTERFACES

Standard

USB, Serial(RS-232C), Ethernet

Optional

Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE)



CERTIFICATIONS

KC, CE, CB, CCC



FONTS / GRAPHICS

EPL II

6 bitmapped

8x12, 10x16, 12x20, 14x24,
32x48, 24x24(KSC5601)

ZPL II

9 bitmapped

5×9, 7×11, 10×18, 10x18, 15×28,
13×26, 40×60, 13x21, 24x24

2 smooth scalable(English, Korean)



ACCESSORIES

Standard

Power Cord, Power Supply,
Interface Cable(USB)

Optional

External Paper Supply,
Auto Cutter

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

