

sewoo

All about rugged design with stable performance

LK-P12II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged Design



Drop Resistant



Easy Loading



127
mm/sec

Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 5ips(127mm/sec)

Print Width

Up to 1.8" (48mm)

Resolution

203 dpi (8dots/mm)

Memory

16MB(Max 64MB)

SDRAM 16MB (MAX.64MB)

Battery Voltage / Capacity

7.4V 2600mAh Li-ion

3.3Hrs Charging time

85Hrs Stand-by

Rechargeable Li-ion battery

Sensor

Paper end, Gap, Black mark,

Cover open, Peeler detect,

Peeler S/W

Reliability

TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

4.1" × 6.22" × 3.34"
(104 × 158 × 85mm)

Weight

1.2lb(580g with battery)



INTERFACES

Standard

USB, Serial(RS-232C)

Optional

Wi-Fi(802.11a/b/g/n), Bluetooth Smart Ready (Bluetooth4.2+BLE)



ACCESSORIES

Standard

USB Cable, Serial Cable,

Recharger, Battery Pack,

Thermal Roll Paper, Belt Clip

Battery Charger (8.4V)

Optional

Shoulder Strap, Vehicle Charger,

Battery Cradle



OPERATING CHARACTERISTICS

Operating Temperature

14 ~ 122°F(-10 ~ 50°C)

Operating Humidity

10 ~ 90%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%

Dust-and Water-resistance Rating

IP42

Drop Rating

4.9ft.(1.5m, Set only) to concrete



BARCODES

1D

EAN-8, EAN-8(+2+5), EAN-13,

EAN-13(+2+5), Codabar, Code11,

Code39, Code93, Code128,ITF,

LUPC-A(+2+5), UPC-E, UPC-E(+2+5),

Planet, UPC-A etc

2D

QR, PDF417, MicroPDF417, Maxicode,

Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations

ESC/POS, CPCL, ZPL Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Window CE & Mobile Driver & SDK

(CE 4.2~, Mobile 5.0~), Linux Driver,

Mac Driver, OPOS Driver,

JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type

Thermal paper/label

Media Width

0.5"~ 2.2"(12.7~58mm)

Media Core Diameter

Ø 0.4" (12.5mm ± 0.5mm)

Media Roll Diameter

Ø 2.2"(56mm)

Thickness

0.06~0.16mm



FONTS / GRAPHICS

Character Size

Font A(12×24), Font B(9×17),

Asian Font(KOR,JPN,CHN-GB2312,

CHNBig5), Font0/1/2/4/5/6/7,

Resident TTF, Downloadable TTF,

FontA~H, FontGS, Residnt TTF(Font0),

Font 1~8

Characters per line (CPL)

Font A(12x24): 32cpl,

Font B(9x17): 42cpl

Character set

95 Alphanumeric,

14 International,

128 * 18 page



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL,

Mfi, UKCA,BCS

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuahtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

