

sewoo

Cost-effective and Light weight receipt printer

LK-P34L



- Fast Print Speed : 4 ips
- Excellent Compatibility
- NFC for easy Bluetooth pairing
- Durable and resistant to water and dust
- S-Linerless solution supported
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Belt Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Drop
Resistant



Easy
Loading



Fast
Speed



Compact
Design



Easy
Maintenance



Improved
Battery Life



S-MDM
Support



S-Linerless
Solution Support

APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
Up to 4ips (100mm/sec)

Print Width
Up to 2.8" (72mm)

Resolution
203 dpi (8dots/mm)

Memory
8MB(Max 64MB)
SDRAM 8MB (MAX.16MB)

Battery Voltage / Capacity
7.4V / 2,000mAh.
Rechargeable Li-ion battery

Battery Charging Time
Max. 2.7 Hrs

Standby Time
Max. 61 Hrs

Sensor
Paper end , Black Mark sensor

Reliability
TPH life : 50km

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
4.23" x 5.70" x 2.20"
(107.5 x 145 x 56mm)

Weight
0.85lbs /390g (Battery Incl.)

INTERFACES

Standard
USB 2.0

Optional
Wi-Fi(802.11a/b/g/n), Bluetooth Smart
Ready (Bluetooth4.2+BLE), NFC Tag

CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL,
Mfi, UKCA,BCS

OPERATING CHARACTERISTICS

Operating Temperature
14~122°F (-10 ~ 50°C)

Operating Humidity
10 ~ 80%

Storage Temperature
-4~140°F (-20 ~ 60°C)

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP54

Drop Rating
5ft/1.5m (set only) to concrete

BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
LUPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, UPC-A etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39

SOFTWARE

Emulations
ESC/POS, CPCL, ZPL Command
compatible

Drivers
Windows Driver(XP ~, Server2003 ~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver,
JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK

MEDIA CHARACTERISTICS

Media Type
Thermal paper/Label,
Linerless(Max. Restick)

Media Width
3.1" (80mm)

Media Core Diameter
0.4" (12.5mm ± 0.5mm)

Media Roll Diameter
Ø 2.0"(50mm)

Thickness
0.06 ~ 0.16mm

Fonts / GRAPHICS

Character Type
Font A(12x24), Font B(9x17), Asian Font
(KOR, JPN, CHN-GB2312, CHN-Big5),
Font0/1/2/4/5/6/7, Resident TTF ,
Downloadable TTF, FontA~H, FontGS,
Residnt TTF(Font0), Font 1~8

Characters per line (CPL)
Font A(12x24): 48cpl,
Font B(9x17): 64cpl,

Character set
95 Alphanumeric, 14 International,
128 x 18 Graphic

ACCESSORIES

Standard
USB Cable, Battery pack,
Thermal roll paper, Belt strap,
Battery Charger (8.4V)

Optional
4bay cradle, Battery cradle,
Shoulder Strap, Leather Case

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprinter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com

