

sewoo

3-Inch POS Printer

SLK-TS200



- Simple and sleek design
- High Performance Easy Maintenance
- Wheel-type paper jam control
- High speed printing at 250mm/sec
- Visible wireless connectivity status
- Ideal for top exit printing with wall mount
- Simple and easy replacement of components including head, motor, cutter, PCB, etc



WiFi




Bluetooth



Barcode



Durable



Paper Width



Easy Loading



Fast Speed



Compact Design



Easy Maintenance

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

250mm/sec

Print Width

72mm(576 Dots/Line)

Resolution

203 dpi

Direction

Unidirectional with friction feed

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 2.5A

Sensor

Paper end, Cover open,

Reliability

TPH life : 150km

MCBF : 80 Million lines

Auto cutter

Type : Guillotine

Life : 1,500,000 cuts

Cutting method: Partial / Full cut

Cashdrawer

1 circuit(24V, Max. 1A),

2 circuit(24V, Max. 1A)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

136×174×132mm

(5.35"×6.85"×5.19")

Weight

1.04kg



INTERFACES

Standard

1. USB(B type)+Serial(RS- 232C_9pin)

+Ethernet Built-in

2. USB(B type)+Serial(RS232C-9Pin)

+RJ45(Serial)

Optional

Bluetooth Smart Ready

(Bluetooth5.0+BLE) or

WiFi(802.11 a/b/g/n)



CERTIFICATIONS

KC, CE, FCC, IC, CB, NRTL



OPERATING CHARACTERISTICS

Operating Temperature

0 ~ 45°C

Operating Humidity

10 ~ 80%

Storage Temperature

-10 ~ 60°C

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Media Width

80mm

Media Core Diameter

12.5mm ± 0.5mm

Media Roll Diameter

Max. ø 83mm

Thickness

0.06 ~ 0.08mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Linux Driver, Mac Driver, OPOS Driver,

JavaPOS Driver

SDK

Android SDK, iOS SDK, Windows SDK



BARCODES

1D

EAN-8, EAN-13, Code 39, Code 93,

Code 128, ITF, UPC-A, UPC-E,

Codabar

2D

PDF 417, QR code



FONTS / GRAPHICS

Characters per line (CPL)

Font A(12x24) :

48 columns / 42columns

Font B(9x17) :

64 columns / 56 columns

Character set

Alpha numeric character : 95

Expanded graphic :

128 x 18 Page (1 space page)

International character : 16



ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Optional

Melody Box, 24V Buzzer,

Paper Guide

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-859-992-5936

E. NA_Sales@miniprnter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

E. LA_Sales@miniprnter.com

M. +52-1-55-3232-9543

