

sewoo

Compact size and Enhanced usability

# SLK-TS400



- Structure for easy maintenance
- Design for enhanced usability
- Compact footprint to help easily fit on the counter.
- Ideal for front exit printing with Wall mount.
- Supports flexible printing exit way Front exit or top exit.
- Ideal for kitchen/bar printer with melody box(Kitchen buzzer)
- Easy handling the jam of the paper with same cover opening/closing direction as paper cutting direction.



Rugged Design




Drop Resistant



Barcode



Durable



Paper Width



Easy Loading



High Speed



Compact Design



Easy Maintenance



Various interface



## APPLICATION



## SPECIFICATIONS

### **PRINTER CHARACTERISTICS**

#### Print Method

Direct thermal

#### Print Speed

Up to 8.6ips(220mm/sec)

#### Print Width

Up to 2.8" (72mm)

#### Resolution

180 dpi

#### Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

#### Sensor

Paper end, Cover open

#### Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 1.5 Million cuts

#### Drawer port

2 circuits(24V, 1A Max.)

### **PHYSICAL CHARACTERISTICS**

#### Dimension (W x D x H)

5.11"×5.51"×6.06"  
(130×140×154mm)

#### Weight

2.7lb(1.25Kg)

### **INTERFACES**

#### Standard

USB(B type)+Serial

(RS-232C\_25pin)Built-in,

USB(B type)+Ethernet Built-in

### **CERTIFICATIONS**

CE, FCC, KC, UL/cUL, CB,  
ENERGY STAR, TELEC

### **OPERATING CHARACTERISTICS**

#### Operating Temperature

32 ~ 113°F(0 ~ 45°C)

#### Operating Humidity

35 ~ 80%

#### Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

#### Storage Humidity

10 ~ 90%

### **MEDIA CHARACTERISTICS**

#### Media Type

Thermal receipt paper

#### Media Width

3.14"(80mm)

#### Media Core Diameter

0.4"(12.5mm)

#### Media Roll Diameter

3.1"(ø 83mm)

#### Thickness

0.06~0.09mm

### **SOFTWARE**

#### Emulations

ESC/POS

#### Drivers

Windows Driver(XP ~, Server2003 ~),  
Windows CE & Mobile Driver (CE 4.2 ~,  
Mobile 5.0 ~), Linux Driver, Mac Driver,  
OPOS Driver, JavaPOS Driver, iOS SDK,  
Android(6.0 ~) SDK, Windows SDK,  
Windows CE SDK, Linux SDK

### **BARCODES**

#### 1D

EAN-8, EAN-13, Code 39, Code 93,  
Code 128, ITF, UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code, DATA MATRIX

### **FONTS / GRAPHICS**

#### Character Type

Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

#### Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic

### **ACCESSORIES**

#### Standard

Power Adaptor 24Vdc / 1.75A

#### Option

Melody box, 24V Buzzer

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_Sales@miniprnter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA\_Sales@miniprnter.com

