


Rugged i9000S Smart POS Payment Terminal

5" HD / 2" Thermal printer
Safedroid OS / 4G
MSR / Chip card / NFC
Rugged Design



Enterprise Security

Safedroid OS (based on Android 5.1)
Supports 2 SAM slots
EMV L1/L2 certified
EMV contactless

Multiple Payment Solutions

MSR, Chip card, NFC
2D payment
Membership rewards point

Advance Capacitive Screen

5" HD(720x1280)
Industrial grade sensitivity,
works with gloves and wet fingers.

Thermal Printer

2" thermal printer
30/40mm paper roll
Supports 2D barcode printing

Powerful Data Collection


Optional 1D or 2D scan engine
5MP/8MP camera
GPS positioning

Voice and Data Connection

2G/3G/4G
802.11 a/b/g/n WiFi

UROVO i9000S Specification

Basic Characteristics	O.S	Safedroid OS (based on Android 5.1), supports multi-language
	CPU	Quad-Core 1.2GHz
	Display	5.0 inch TFT-LCD HD (720 x 1280) color screen
	Panel	Ultra sensitive capacitive touch screen, can work with gloves and wet fingers
	RAM	2GB
	ROM	16GB
	Dimensions	184mm x 81 mm x 32mm (max 51mm)
	Weight	550g (Battery included)
	Buttons	Front: User define button x 1, Cancel button x 1, Confirm button x 1 , Clear button x 1 Side: SCAN button x 2, The volume switch button, ON / OFF button
	Input	Chinese / English, and supports handwriting and soft keyboard
Barcode Scanner	1D Laser	Code 39; Codabar; Code 128; Discrete 2 of 5; IATA 2 of 5; Interleaved 2 of 5; Code 93; UPC A; UPC E0; EAN 8; EAN 13; MSI; EAN 128; UPC E1; Trioptic Code 39; Bookland EAN; Coupon Code; RSS-Limited; RSS-14; RSS-Expanded. 1D Symbolologies: UPC/EAN, Bookland EAN, UCC Coupon Code, ESSN EAN, CODE 39, CODE 128, GS1-128, ISBT 128, Trioptic Code 39, CODABAR, MSI, Interleaved 2/5, Discrete 2/5, Chinese2/5, Korean3/5, Matrix 2/5, CODE 32, CODE 93, CODE 11, Inverse 1D, GS1 DataBar, Composite Codes;
	2D CMOS (Optional)	2D Symbolologies: PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse, MaxiCode, QR Code, Aztec, Aztec Inverse; Postal Codes: U.S. Postne, U.S. Planet; U.K. Postal; Japan Postal; Australian Postal; Netherlands KIX Code; USPS 4CB/One Code/Intelligent Mail; UPU FICS Postal.
Power	Main Battery	Rechargeable 3.8V, 5000mAh lithium polymer battery pack (Typical Operation time ≥8 hours)
	RTC Battery	Real time clock battery
Radio Communication	Wi-Fi	802.11 a/b/g/n wireless communication
	Bluetooth	Bluetooth 4.1
	4G	TDD-LTE: B40 FDD-FTE: B1/B2/B3/B4/B5/B7/B8/B20
	3G	UMTS(WCDMA)/ HSPA+: 850/900/1900/2100MHz
Payment	2G	GSM/EDGE/GPRS/CDMA: 850/900/1800/1900MHz
	Magcard	Supports ISO7811/7812/7813, and supports triple track (tracks 1/ 2/ 3), bi-directional
	Chip Card	Supports ISO7816 standard
	Contactless Cards(RFID)	Supports 14443A / 14443B; Supports 10MHz~20MHz frequency, and reading time less than 300 milliseconds
Expansion and peripherals	Printer	58mm printing paper, 203dpi / 8dot / mm; Printing speed: 50~70mm/s, and supports barcode printing 30/40mm paper roll
	Camera	5MP/8MP camera with LED flash and auto-focus function
	GPS	GPS, Supports A-GPS.
	Slot	Micro SD/TF x 1(a maximum of 32 GB), SIM x 1, SAM x 2
Accessories	Interfaces	Mini USB x 1, Pogo pin x 1, 3.5mm Audio Jack x 1, DC Jack
	Audio Frequency	Microphone, Earpiece, Speaker
	Standard	Power adaptor, Data line, One battery.
User Environment	Optional	Cradle, Carrying Pouch, Wrist Strap, Stylus, Paper roll.
	Operating Temperature	-10~50°C (14~122°F)
	Storage Temperature	-20~70°C (-4~158°F)
	Humidity	5% ~ 95% (non condensing)
Product Certification	Drop Durability	1.2m
	CCC, FCC, CE,ROHS, EMV4.3 Level1&2, EMV CONTACTLESS, PCI PTS4.1 PAYPASS, PAYWAVE, AMEX CONTACTLESS	



Multifunctional docking station



Handstrap



Fingerprints
Biometric Module



Battery charger

Urovo Technology Corporation Limited

For more information, please visit <http://www.urovo.com/en>

For purchasing or partnership enquiry, please +86 755-22673926 urovo@urovo.com